



Interflon Fin Lube TF (Aerosol)

Highly Versatile, extremely durable dry-film Lubricant

Product description

Highly versatile, industrial quality dry film lubricant with Teflon®. Forms a highly durable lubrication film that virtually eliminates wear on moving parts. Goes on wet, cleanses, displaces moisture, breaks down deposits and penetrates even into the most inaccessible areas. Loosens seized, rusted and frozen parts and prevents the formation rust and other corrosives. Holds up to high pressures, resists water wash-off and will not attract dirt, dust and other abrasives.

Is approved by Arnold & Stolzenberg.

Application

Where parts are exposed to contamination or moisture, need to be coated to prevent rust & corrosion or where conventional lubricants fling off. Excellent choice for the lubrication of chains, cables, sliding tracks, (air) tools, joints, pivots, cams, belts, saws, guides, springs, pulleys, threaded parts, bolts, rollers, taps, pins, bushings, valves, conveyors and much, much more.

Advantages

- less wear
- no stick slip
- no dirt adhesion
- water resistant
- strong penetrating
- good corrosion protection
- long lasting lubrication
- excellent rust solvent

Instructions for use

Parts should be cleaned first with an organic or alkaline cleaning agent. Shake gently before use. Spray Fin Lube TF onto parts and allow to penetrate. The longer the penetration time the longer the time between lubrications. Regular use of Fin Lube TF extends the life of the chain dramatically. Note: do not use too much Fin Lube TF. A thin layer, with occasional re-application now and again, works better than a thick layer. Remove redundant Fin Lube TF with a cloth.

Safety regulations

The product has been classified and marked in accordance with EU Directives / Ordinance on



Hazardous Materials.
See Material Safety Data Sheet.

Packaging

See our current article list.

Transport regulations

See Material Safety Data Sheet.

Technical data

Basic components :	Mixture of mineral and synthetic oil, paraffinic solvent, Teflon®* and additives
Density @20°C ASTM D4052 :	0.86 g/ml (oil)
ISO VG :	n.a.
Dynamic viscosity @20°C ASTM D2983 :	70 mPas (oil)
Kinematic viscosity @40°C ASTM D445 :	n.a.
Colour :	yellow brown / cloudy
Odour :	oily
Pour point ASTM D97 :	< -43°C (oil)
Temperature range :	-43°C up to 170°C**
Friction coefficient :	(Teflon®*) 0.02-0.06
Biological degradability (according to ASTM D7373-07) :	inherent biodegradable
Shelf life :	4 years***
Aerosol:	
Vapour pressure @ 20°C :	4,2 bar
Propellant :	propane/butane

** High temperature limit is valid after evaporation of solvent.

*** Usable life of the product when stored at room temperature in the original and unopened packaging.



Interflon Fin Lube TF (Aerosol)

**INTERFLON B.V., P.O. Box 1070
NL-4700 BB Roosendaal, The Netherlands
Tel. (31) 165 55 39 11 / Fax (31) 165 53 80 82 / www.interflon.com**

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.
Teflon® is a registered trademark of E.I. DuPont de Nemours
Interflon® is a registered trademark of Interflon bv

Interflon reference nr.: ENT8238014/04/2004